


DARKBUSTER LED-12

DARKBUSTER LED-5 DARKBUSTER LED-3

CE FC RoHS 



- ◆ Waterproof level: 300 ft
- ◆ Rechargeable & Japan PSE li-ion battery (LED-5 & LED-12 only)
- ◆ Aluminum body (LED-3 & LED-5 only)
- ◆ Super compact
- ◆ Switchable lens: 15° or 25° (LED-3 & LED-5 only)
- ◆ 3 operation modes: Turbo / General / Strobe (LED-3 only)



Specification & Features

Model	Power	Lamp	Brightness	Battery	Run Time
DARKBUSTER LED-12	12W	High-Intensity LED	700Lm	4.4A / 2.2A Li-ion battery	4.4A: 240 mins ; 2.2A: 145 mins
DARKBUSTER LED-5	5W		210Lm	Li-ion battery	210 mins
DARKBUSTER LED-3	3W		170Lm	3 Alkaline AAA	Strobe mode: 24 hrs ; General mode: 12 hrs ; Turbo mode: 6 hrs

Model	LED Life	Size	Weight	Test depth	Switchable lens
DARKBUSTER LED-12	50,000 hrs	Ø7.8 x L20.5cm	4.4A: 870 g ; 2.2A: 730 g	100m / 300ft	none
DARKBUSTER LED-5		Ø3.67 x L15 cm	200 g (excluding battery)		15° or 25°
DARKBUSTER LED-3		Ø3.67 x L13 cm	130 g (excluding battery)		15° or 25°

All specifications present approximately and subject to change without notice. Please check with the BRIGHTSTAR website for exact offers. Part of the data is provided by the original manufacturer.

Option



Adapter set (LED-3 / LED-5 only for DB/DB JR/E1)

EX. →



Parts



- DARKBUSTER LED-12**
- 1 light body with rubber overmold
 - 2 diffusion glass filter
 - 3 lantern grip
 - 4 Ac to DC adapter
 - 5 carrying cord
 - 6 tool set



- DARKBUSTER LED-5**
- 1 adapter
 - 2 charger
 - 3 light body
 - 4 plastic hook
 - 5 li-ion battery



- DARKBUSTER LED-3**
- 1 plastic hook
 - 2 battery
 - 3 light body

PRODUCT ORDER CODE

DARKBUSTER LED-12

12W/2200 mA	D30112220
12W/4400 mA	D30112440

DARKBUSTER LED-5

5W	D30105150	15°
	D30105250	25°

DARKBUSTER LED-3

3W	D30103150	15°
	D30103250	25°

NOTE
15° : switchable len
25° : switchable len